

交直流
600A

钳形表

真有效值 | NCV测量



探索·创新 Explore&Innovation
专业环境仪器仪表测试专家

TASI® 特安斯

专注于数字仪表领域开发与生产
专业品质 100%放心选购

PRODUCT FEATURES

1. AC and DC 600A
2. With NCV non-contact voltage sensing function;
3. With flashlight lighting function;
4. Use single-chip microcomputer to control the backlight on and off, and automatic shutdown on and off, to meet the needs of different occasions;
5. Full protection function, anti high voltage ignition circuit design;

Product features

Basic function	Range	Basic precision			
		TA8315A	TA8315B	TA8315C	TA8315D
Model		TA8315A	TA8315B	TA8315C	TA8315D
DC voltage	6V/60V/600V/600V	±(0.5%+3)	±(0.5%+3)	±(0.5%+3)	±(0.5%+3)
AC voltage	6V/60V/600V/600V	±(0.5%+5)	±(0.5%+5)	±(0.5%+5)	±(0.5%+5)
AC current	6A/60A/600A	±(2%+30)	±(2%+30)	±(2%+30)	±(2%+30)
DC current	60A/600A	-	-	-	±(2%+30)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/40MΩ	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)	±(0.8%+3)
Capacitance	60nF/600nF/6uF/600uF/6mF/30mF	-	-	±(2.0%+8)	±(2.0%+8)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	-	±(0.01%+2)	±(0.01%+2)	±(0.01%+2)
Temperature	-20°C-1300°C (-4°F-1832°F)	-	√	√	±(1.2%+3)
Display		4000 digits	6000 digits	6000 digits	6000 digits
Diode		√	√	√	√
Buzzer		√	√	√	√
Backlight		√	√	√	√
square-wave output		-	-	√	√
NCV measurement		√	√	√	√
Flashlight lighting		-	√	√	√
Automatic shutdown		√	√	√	√
Power Supply	2 sections of AAA batteries	√	√	√	√