

HT208A

6000 Counts AC Digital Clamp Meter

NEW



Specifications	Range	Accuracy
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+3)
AC Voltage	600mV/6V/60V/600V/750V	±(0.8%+3)
AC Current	60A/600A/1000A	±(2.5%+5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/ 6MΩ/60MΩ	±(0.8%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/ 1mF/10mF/100mF	±(3.0%+3)
Frequency	10Hz/100Hz/1kHz/10kHz/ 100kHz/1MHz/10MHz	±(0.5%+5)
Duty	1%~99%	±(1.0%+2)
Temperature (°C/°F)	-40°C~1000°C -40°F~1832°F	±(1.0%+2)
Counts		6000 Counts
Auto/Manual range		✓
Continuity		✓
Diode		✓
Data hold		✓
NCV		✓
Back light		✓
Flashlight		✓
DCA ZERO		✓
Low battery indication		✓
Auto power off		✓
True RMS		✓
VFD		✓
INRUSH		✓
MAX/MIN		✓
REL		✓
LowZ		✓
VA-LCD		
Power	3xAAA(1.5V)Batteries	
Weight	Approx. 380g	
Size	240mmX85mmX47mm	
Jaw Size	ø35mmX60mm	
Safety Rating	EN61010-1,-2-030 EN61010-2-033, EN61326-1 CAT III 1000V,CATIV 600V	



HT208D

6000 Counts AC/DC Digital Clamp Meter

NEW

Specifications	Range	Accuracy
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+3)
AC Voltage	600mV/6V/60V/600V/750V	±(0.8%+3)
DC Current	60A/600A/1000A	±(2.5%+5)
AC Current	60A/600A/1000A	±(2.5%+5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/ 6MΩ/60MΩ	±(0.8%+3)
Capacitance	10nF/100nF/1μF/10μF/100μF/ 1mF/10mF/100mF	±(3.0%+3)
Frequency	10Hz/100Hz/1kHz/10kHz/ 100kHz/1MHz/10MHz	±(0.5%+5)
Duty	1%~99%	±(1.0%+2)
Temperature (°C/°F)	-40°C~1000°C -40°F~1832°F	±(1.0%+2)
Counts		6000 Counts
Auto/Manual range		✓
Continuity		✓
Diode		✓
Data hold		✓
NCV		✓
Back light		✓
Flashlight		✓
DCA ZERO		✓
Low battery indication		✓
Auto power off		✓
True RMS		✓
VFD		✓
INRUSH		✓
MAX/MIN		✓
REL		✓
LowZ		✓
VA-LCD		
Power	3xAAA(1.5V)Batteries	
Weight	Approx. 380g	
Size	240mmX85mmX47mm	
Jaw Size	ø35mmX60mm	
Safety Rating	EN61010-1,-2-030 EN61010-2-033, EN61326-1 CAT III 1000V,CATIV 600V	

